

NOTES:

- TREES AND HARDSCAPE IN PLANTER STRIP SUBJECT TO APPROVAL OF THE CITY ENGINEER.
 CONSTRUCTION IN PLANTER STRIP SUBJECT TO ENCROACHMENT PERMIT FROM ENGINEERING DIVISION.
- 2. FOR CURB AND SIDEWALK SCORING SEE SD-8. CONCRETE SHALL BE 6-SACK.
- 3. WHEN FACE OF CURB TO PROPERTY LINE EQUALS 10', SIDEWALK SHALL BE 4'-6" AND PLANTER STRIP SHALL BE 5'-0".
- 4. IF DRIVEWAY AND CURBS ARE NOT PLACED IN MONOLITHIC POUR USE NO. 3 REBAR DOWELS 12" LONG @ 2'-0" ON CENTER. EPOXY IF DRILLED.
- 5. LIMITS OF THE REMOVAL OF EXISTING CURB, GUTTER, SIDEWALK AND ASPHALT SHALL BE DETERMINED IN THE FIELD BY THE CITY INSPECTOR.

			CITY OF FREMONT STANDARD DETAILS			DATE APPROVED BY CITY COUNCIL 04/11/06 RESOLUTION NO. 2006-31		
			TYPE "A" DRIVEWAY APPROACH				200001	,
NO.	REVISED	DATE	RESIDENTIAL				Man Hughes	
	REVISIONS	·					CITY ENGINEER	
FILE NO.		SCALE		DRAWN	CHECKED	DATE	DWG NO.	
SD-10A-06.DWG		AS SHOWN		DC	KC	04/11/06	SD-10A	1 of 1